Permit to Operation - Groveton Group has been granted a Permit to Operate for U.E. Boller #5 Intervention of public the section of t	Cou Peri STA	hit No PO-B hty Coos hit Fee\$200 TE OF NEW HAI esources Agence	.00 S	AMENDED FOR 02 SIP REVISION		
James River Corporation - Groveton Group has been granted a Permit to Operate for C.E. Boller #5 Intermediate Sector (ABCA + 6). Siled mith this A genore under How 15, 19 Intermediate Sector (ABCA + 6). Siled mith this A genore under How 15, 19 Intermediate Sector (ABCA + 6). Siled mith this A genore under How 15, 19 Intermediate Sector (ABCA + 6). Siled mith this A genore under How 15, 19 Intermediate Sector (ABCA + 6). Siled mith this A genore under How 15, 19 This possible sector (ABCA + 6). Siled mith this A genore under How 15, 19 This possible sector (ABCA + 6). Siled mith this A genore under How 15, 19 The possible sector (ABCA + 6). Siled mith this A genore under How 15, 19 The possible sector (ABCA + 6). Siled mith this A genore under How 10, 100, 100, 100, 100, 100, 100, 100,	P	ermit	to Op	erate		
has been granted a Permit to Operate for U.E. Boller #5	This	Certifies that James	River Corporat	ion - Groveton G	roup	•
Request for pormit real lie cubject to Agency of furning the most for most be and must be accounted by the appropriate quipe of the desire	has				· .	•
Request for pormit real in the cubject to Agency of firements and must be accompanied by the oppropriate quipe arregistration forms. This possible cubic cubic distribution of the cubic cu		pasoat-pogiato	- uis-pollutanto tion forme (A.D(A 1 A) filed mith t	bis-Agency ung	er
1. The emission of and 1200; DADI Air 1402 2. The maximum operating rate is limited to: 200 301 302 303 304 305 305 306 307 308 309 309 309 309 309 309 309 309 309 309 309 309 309 309 309 309 309 309 300 301 302 303 304 304 305 305 306 307 308 309 309 309 309 309 309 309 309 309 300 300 <		essentia mith	RGA 105-0-64h	New Househire		mended-190 6
The emission of and 1200; DADT Air 1402 The maximum operating rate is limited to:	Roq	ect for permit	renotrel is subje	et to Ageney serial	rements and m	
2. The maximum operating rate is limited to: 720 720 of <u>#6 fuel oil</u> <u>at 2.2% sulfur, maximum</u> Content is an example and in the second sec	This loga	permit-le-valid- y-enferecable-e		in Rome Sthrough	erdance with all- below:	the.
of <u>#6 fuel oil</u> <u>at 2.2% sulfur, maximum</u> <u>24 urs/day 200</u> 5. Other conditions A. The Boiler Plant (Boilers #1, #2, #4, and #5) and the Recovery System Kiln are limited to emissions equivalent to those from burning 25,000 total gallons per day of fuel oil with 2.2% sulfur content. A daily log of total equivalent oil usage shall be main- tained and available at the Groveton facility for inspection by	aion	e emission of		Limited by DLLA	B Resources C	ommis- Lours
of <u>#6 fuel oil</u> <u>at</u> <u>2.2% sulfur, maximum</u> <u>24 urs/day</u> <u>200</u> <u>40 days/</u> <u>5 Other conditions</u> <u>A. The Boiler Plant (Boilers #1, #2, #4, and #5) and the Recovery</u> System Kiln are limited to emissions equivalent to those from burning 25,000 total gallons per day of fuel oil with 2.2% sulfur content. A daily log of total equivalent oil usage shall be main- tained and available at the Groveton facility for inspection by	Ċ	Pomission of Pomission of Procession Anno	and 1200; DAD	Air 1902	Decouross C	ommis- icilews:
5. Other conditions A. The Boiler Plant (Boilers #1, #2, #4, and #5) and the Recovery System Kiln are limited to emissions equivalent to those from burning 25,000 total gallons per day of fuel oil with 2.2% sulfur content. A daily log of total equivalent oil usage shall be main- tained and available at the Groveton facility for inspection by	Z	e maximum o	perating rate is l	imited to:	Decourses C	
5. Other conditions A. The Boiler Plant (Boilers #1, #2, #4, and #5) and the Recovery System Kiln are limited to emissions equivalent to those from burning 25,000 total gallons per day of fuel oil with 2.2% sulfur content. A daily log of total equivalent oil usage shall be main- tained and available at the Groveton facility for inspection by	Z	e maximum o	perating rate is l	imited to:	maximum	
	Z	#6 fuel o	perating rate is 1 	imited to: t2.2% sulfur,	maximum	
	2. T of . 5. O Sys bur con tai	#6 fuel o #6 fuel o #6 fuel o 24 1137 her conditions The Boiler P em Kiin are ing 25,000 t ent. A dail ed and avail NHARA.	perating rate is 1 	imited to: t 2.2% sulfur, t 2.2% sulfur, t 2.2% sulfur, t 2.2% sulfur, t 1, #2, #4, and ssions equivalent er day of fuel o equivalent oil	#5) and the R t to those fr il with 2.2% usage shall b for inspectio	om sulfur e main-
proprioting and the device connect by this part is made with the depart of the depart of the device device and the ship are in the second s	2. T of . 5. O A. Sys bur Con tai	#6 fuel o #6 fuel o #6 fuel o 24 1137 her conditions The Boiler P em Kiin are ing 25,000 t ent. A dail ed and avail NHARA.	perating rate is 1 	imited to: 	#5) and the R t to those fr il with 2.2% usage shall b for inspectio	om sulfur e main-
	2. T of . 5. O Sys bur Con tai	#6 fuel o #6 fuel o #6 fuel o 24 1137 her conditions The Boiler P em Kiin are ing 25,000 t ent. A dail ed and avail NHARA.	perating rate is 1 	imited to: 	#5) and the R t to those fr il with 2.2% usage shall b for inspectio	om sulfur e main-

James River Corporation Groveton Group

ATTACHMENT

<u>PO-B-215</u> C.E. Boiler #5

Condition A continued

Oil usage for Boiler #5 is to be calculated as follows:

Oil Usage = (Actual Gallons Burned) X

(Ratio of Actual Sulfur Content of Fuel Burned to 2.2)

Where: Actual Gallons Burned are derived from steam production data and Actual Sulfur Content is derived from the maximum sulfur content of the three most recent fuel supplier certificates.

Dated: September 6, 1985