



US EPA CAMPUS RAINWORKS

# INTEGRATING GREEN INFRASTRUCTURE IN CAMPUS PLANNING

APPENDIX: DESIGN TOOLKIT



# ABOUT THIS DESIGN TOOLKIT


The intent of this toolkit is to provide campus stakeholders a starting point to identify, discuss, and evaluate common green infrastructure approaches based on their suitability to site conditions. It includes two principal components:

1. A green infrastructure catalogue, which identifies, visualizes, and describes a range of design options that may be applicable for campus environments.
2. A prioritization matrix, which offers an approach to compare potential green infrastructure measures for their applicability and compatibility with campus conditions.


University professors, students and facility managers have successfully used this toolkit to advance implementation of green infrastructure on their campuses while engaging in planning and engagement activities.

# GREEN INFRASTRUCTURE DESIGN OPTIONS

Upper watershed strategies □□  
 Middle watershed strategies □□  
 Lower watershed strategies □□




■ ■ Downspout Disconnect



■ ■ Rainwater Harvesting




■ ■ Green Roofs




■ ■ Permeable Pavers / Surfaces




■ ■ Flow-Through Planters



■ ■ Dry Bioswales




■ ■ Wet Bioswales




■ ■ Infiltration Trench



■ ■ Oil / Grit Separator



■ ■ Underground Filter



■ ■ Dry Well



■ ■ Bioretention



■ ■ Organic Filter




■ ■ Surface Sand Filters



■ ■ Dry Detention Pond



■ ■ Extended Dry Detention Pond




■ ■ Wet Pond



■ ■ Pocket Pond



■ ■ Pocket Stormwater Wetland




■ ■ Stormwater Wetland



■ ■ Site Reforestation / Revegetation



■ ■ Stream Restoration




■ ■ Flood Management Area

# GREEN INFRASTRUCTURE DESIGN OPTIONS

Unless noted, all definitions below are derived from the *Georgia Stormwater Management Manual, Volume 2 Technical Handbook (2016)* ([link](#))


Upper watershed strategies ■ ■ ■  
 Middle watershed strategies ■ ■ ■  
 Lower watershed strategies ■ ■ ■



## Stormwater Wetland

Stormwater wetlands are constructed wetland systems used for stormwater management. Stormwater wetlands consist of a combination of shallow marsh areas, open water, and semi-wet areas above the permanent water surface. As stormwater runoff flows through a wetland, it is treated, primarily through gravitational settling and biological uptake.


■ ■ ■ Stormwater Wetland



## Downspout Disconnect

A downspout disconnect spreads rooftop runoff from individual downspouts across lawns, vegetated areas, and other pervious areas, where the runoff is slowed, filtered, and can infiltrate into the native soils.

■ ■ ■ Downspout Disconnect



## Dry Bioswale

Dry swales are vegetated open channels that are designed and constructed to capture and treat stormwater runoff within dry cells formed by check dams or other structures. A dry swale is designed to prevent standing water, with or without an underdrain.

■ ■ ■ Dry Bioswales



## Surface Sand Filters

Sand filters are multi-chamber structures designed to treat stormwater runoff through filtration, using a sand bed as its primary filter media. Filtered runoff may be returned to the conveyance system through an underdrain system, or allowed to partially exfiltrate into the soil.

■ ■ ■ Surface Sand Filters



# GREEN INFRASTRUCTURE DESIGN OPTIONS

Unless noted, all definitions below are derived from the *Georgia Stormwater Management Manual, Volume 2 Technical Handbook (2016)* ([link](#))

Upper watershed strategies ■ ■ ■  
 Middle watershed strategies ■ ■ ■  
 Lower watershed strategies ■ ■ ■




## Stream Restoration

Stream restoration is often performed to reduce the effects of stressors on the environment and return stream structure and function to pre-disturbance conditions. Often, restoration projects aim to improve water quality and in-stream habitat, manage riparian zones, stabilize stream banks, and allow fish to pass barriers.

Source: [www.enviro.wiki/index.hp?title=Stream\\_Restoration](http://www.enviro.wiki/index.hp?title=Stream_Restoration)


■ ■ ■ Stream Restoration



## Rainwater Harvesting

Rainwater harvesting is a common stormwater management practice used to catch rainfall and store it for later use. Typically, gutters and downspout systems are used to collect the water from roof tops and direct it to a storage tank. Rainwater Harvesting systems can be either above or below the ground. Once captured in the storage tank, the water may be used for non-potable indoor (requires treatment) and outdoor uses.


■ ■ ■ Rainwater Harvesting



## Wet Bioswale

Wet bioswales are vegetated open channels that are designed and constructed to capture and treat stormwater runoff within wet cells formed by check dams or other structures. A wet swale is designed to hold water.

■ ■ ■ Wet Bioswale



## Underground Filter

Underground sand filters are concrete structures designed to store and filter rainwater through sand to remove pollutants collected from rooftops, sidewalks, and roads. Water first filters through an oil/grit trap to remove heavy debris, and then flows through layers of sand and gravel before being released through a pipe into local streams or storm drain system.

Source: [www.montgomerycountymd.gov/DEP/Resources/Files/PostersPamphlets/Structural-Underground-Sand-Filters.pdf](http://www.montgomerycountymd.gov/DEP/Resources/Files/PostersPamphlets/Structural-Underground-Sand-Filters.pdf)

■ ■ ■ Underground Filter



# GREEN INFRASTRUCTURE DESIGN OPTIONS

Unless noted, all definitions below are derived from the *Georgia Stormwater Management Manual, Volume 2 Technical Handbook (2016)* ([link](#))


Upper watershed strategies ■ ■ ■  
 Middle watershed strategies ■ ■  
 Lower watershed strategies ■ ■



## Pocket Pond

A pocket pond is characterized by a small drainage area; the water level is sustained by groundwater during dry weather.


■ ■ Pocket Pond



## Permeable Pavers / Surfaces

A permeable paver system is a pavement surface composed of structural units with void areas that are filled with pervious materials such as gravel, sand, or grass turf. The system is installed over a gravel base course that provides structural support and stores stormwater runoff that infiltrates through the system into underlying permeable soils.

■ ■ ■ Permeable Pavers/ Surfaces




## Pocket Stormwater Wetland

A pocket wetland is used to capture and treat a specific volume of stormwater runoff. This structure is a shallow wetland with a permanent pool and wetland species added to the bottom to enhance the pollutant removal capability. For this BMP, a high groundwater table is used to maintain the shallow pool and wetland vegetation.

Source: [apps.itd.idaho.gov/apps/env/BMP/PDF%20Files%20for%20BMP/Chapter%205/PC-25%20Pocket%20Wetland.pdf](https://apps.itd.idaho.gov/apps/env/BMP/PDF%20Files%20for%20BMP/Chapter%205/PC-25%20Pocket%20Wetland.pdf)

■ ■ Pocket Stormwater Wetland



## Organic Filters

Organic filters are surface media filters that use organic materials, such as leaf compost or a peat/sand mixture, as the filter media. Runoff is filtered through the media prior to discharging through an underdrain system. The Organic media may be able to provide enhanced removal of some contaminants, such as heavy metals.


■ ■ ■ Organic Filters



# GREEN INFRASTRUCTURE DESIGN OPTIONS

Unless noted, all definitions below are derived from the *Georgia Stormwater Management Manual, Volume 2 Technical Handbook (2016)* ([link](#))


Upper watershed strategies ■ □ □  
 Middle watershed strategies □ ■ □  
 Lower watershed strategies □ □ ■



## Oil / Grit Separator

Oil / grit separators are hydrodynamic controls that use the movement of stormwater runoff through a specially-designed structure to remove target pollutants. They are typically used on smaller, impervious, commercial sites and urban hotspots.


■ □ □ Oil Grit Separator



## Infiltration Trench

An infiltration trench is a shallow excavation, typically filled with stone or an engineered soil mix, which is designed to temporarily hold stormwater runoff until it infiltrates into the surrounding soils. Infiltration practices are able to reduce stormwater quantity, recharge the groundwater, and reduce pollutant loads.


■ □ □ Infiltration Trench



## Bioretention

Bioretention areas are shallow stormwater basins or landscaped areas that utilize engineered soils and vegetation to capture and treat stormwater runoff. Bioretention areas may be designed with an underdrain that returns runoff to the conveyance system or designed without an underdrain to exfiltrate runoff into the soil.

■ □ □ Bio Retention



## Flow-Through Planter

Flow-through planters are structures placed above ground with impervious bottoms that are filled with soil and vegetation which allow stormwater to infiltrate through the soil before being discharged. The bottom of a planter contains a porous pipe that drains the stormwater after it has filtered through the soil and vegetation. Planters are typically installed next to buildings or common open areas to treat stormwater from rooftops.

Source: [www.waterboards.ca.gov/publications\\_forms/publications/factsheets/docs/planters\\_fs.pdf](http://www.waterboards.ca.gov/publications_forms/publications/factsheets/docs/planters_fs.pdf)


■ □ □ Flow Through Planter



# GREEN INFRASTRUCTURE DESIGN OPTIONS

Unless noted, all definitions below are derived from the *Georgia Stormwater Management Manual, Volume 2 Technical Handbook (2016)* ([link](#))

Upper watershed strategies ■ □ □  
 Middle watershed strategies □ □ □  
 Lower watershed strategies □ □ □



## Flood Management Area

Flood management areas retain and buffer the effects of heavy rainfall and protect economic activities and communities from flood damage. Natural management areas like flood plains have an important role to play in reducing flood risks and are also the natural habitat of many endangered species. However, they can also be man made areas that can be used for detention such as lowered playing fields.


□ □ ■ Flood Management Area



## Water Squares

When sub-surface crates are full, sunken playgrounds fill up temporarily with additional stormwater run-off. These water squares reduce damage, increase water quality due to combined stormwater reduction and increase recreational activities.


□ □ ■ Water Squares



## Dry Well

Dry wells are shallow excavations, typically filled with stone, that are designed to intercept and temporarily store post-construction stormwater runoff under the ground surface until it infiltrates into the underlying and surrounding soils. If properly designed, they can provide significant reductions in post-construction stormwater runoff rates, volumes, and pollutant loads on development sites.

■ □ □ Dry Well



## Stormwater Pond / Wet Pond

Stormwater ponds are constructed stormwater retention basins that have a permanent pool (or micropool) of water. Some runoff reduction is achieved within a stormwater pond or detention system through evaporation and transpiration. Stormwater ponds provide water quality treatment through sediment precipitation in the permanent pool.

Source: [mde.maryland.gov/programs/Water/StormwaterManagementProgram/Documents/Fact%20Sheets/MDE\\_Fact\\_Sheet\\_S\\_WetPonds.pdf](http://mde.maryland.gov/programs/Water/StormwaterManagementProgram/Documents/Fact%20Sheets/MDE_Fact_Sheet_S_WetPonds.pdf)

□ □ ■ Stormwater Pond/ Wet Pond






# GREEN INFRASTRUCTURE DESIGN OPTIONS

Unless noted, all definitions below are derived from the *Georgia Stormwater Management Manual, Volume 2 Technical Handbook (2016)* ([link](#))


Upper watershed strategies □ □ □  
 Middle watershed strategies □ □ □  
 Lower watershed strategies □ □ □



## Site Reforestation / Revegetation

Reforestation or revegetation is a process of planting trees, shrubs, and other native vegetation in disturbed pervious areas to restore the area to pre-development or better conditions. The process can be used to establish mature native plant communities, such as forests, in pervious areas that have been disturbed by clearing, grading and other land disturbing activities. These plant communities intercept rainfall and slow and filter the stormwater runoff to improve infiltration in the ground. Areas that have been reforested or revegetated should be maintained in an undisturbed, natural state over time. These areas must be designated as conservation areas and protected in perpetuity through a legally enforceable conservation instrument (e.g., conservation easement, deed restriction).

■ ■ ■ Site Revegetation



## Green Roof

Green roofs represent an alternative to traditional impervious roof surfaces and typically consist of underlying waterproofing, drainage systems, and an engineered planting media. Stormwater runoff is captured and temporarily stored in the engineered planting media, where it is subjected to evaporation and transpiration before being conveyed back into the storm drain system. There are two different types of green roof systems. Intensive green roofs have a thick layer of soil, can support a diverse plant community, and may include trees. Extensive green roofs have a much thinner layer of soil that is comprised primarily of drought tolerant vegetation.

■ ■ ■ Green Roof



## Extended Dry Detention Ponds

Extended dry detention basins are modified conventional dry detention ponds, designed to hold stormwater for at least 24 hours to allow solids to settle and to reduce local and downstream flooding. Extended dry detention basins may be designed with either a fixed or adjustable outflow device. Pretreatment is a fundamental design component of an extended dry detention basin to reduce the potential for clogging. Other components such as a micropool or shallow marsh may be added to enhance pollutant removal.

Source: [megamanual.geosyntec.com/npsmanual/drydetentionbasin.aspx](http://megamanual.geosyntec.com/npsmanual/drydetentionbasin.aspx)

□ □ ■ Extended Dry Detention Ponds



## Dry Detention Pond

A dry detention pond is an impoundment or excavated basin for the short-term detention of stormwater runoff from a completed development that allows a controlled release from the structure at downstream, pre-development flow rates. Conventional dry detention basins typically control peak runoff for 2-year and 10-year 24-hour storms. They are not specifically designed to provide extended dewatering times, wet pools, or groundwater recharge. Sometimes flows can be controlled using an outlet pipe but this approach typically cannot control multiple design storms.

Source: [megamanual.geosyntec.com/npsmanual/drydetentionbasin.aspx](http://megamanual.geosyntec.com/npsmanual/drydetentionbasin.aspx)

□ □ ■ Dry Detention Pond



# GREEN INFRASTRUCTURE DESIGN OPTIONS PRIORITIZATION MATRIX

GREEN INFRASTRUCTURE DESIGN OPTIONS (MEASURES, BMPs)	ECOLOGICAL CONSIDERATIONS		ECONOMIC CONSIDERATIONS	
	Location in Watershed	Ecological Co-Benefits	Relative Initial Cost	Relative Maintenance Cost
	Upper, Middle, Lower	Low, Medium, High	\$ / \$\$ / \$\$\$	\$ / \$\$ / \$\$\$
Green Roofs	All	Medium	\$\$\$	\$\$\$
Rainwater Harvesting	All	Low	\$\$	\$
Oil/Grit Separator	All	Low	\$	\$\$
Downspout Disconnect	All	Low	\$	\$\$
Site Reforestation/Revegetation	All	High	\$\$\$	\$
Infiltration Trench	Upper	Medium	\$	\$\$
Permeable Pavers/Surfaces	Upper	Medium	\$\$\$	\$\$
Organic Filter	Upper	Medium	\$\$	\$\$
Surface Sand Filters	Upper	Low	\$\$	\$\$
Bioretention	Upper/Middle	High	\$\$\$	\$\$
Flow-Through Planters/Landscape Infiltration	Upper/Middle	Medium	\$\$	\$
Dry Well	Upper/Middle	Medium	\$\$	\$\$
Dry Bioswales	Middle	Medium	\$\$\$	\$\$
Wet Bioswales	Middle	Medium	\$\$\$	\$\$
Dry Detention Pond	Lower	Medium	\$	\$\$
Extended Dry Detention Pond	Lower	Medium	\$	\$\$
Wet Pond	Lower	High	\$	\$\$
Pocket Pond	Lower	Medium	\$	\$\$
Underground Filter	Lower	Low	\$\$	\$
Flood Management Area	Lower	Low	\$	\$
Stormwater Wetland	Lower	High	\$\$	\$
Pocket Stormwater Wetland	Lower	Medium	\$\$	\$
Stream Restoration	Lower	High	\$\$\$	\$

Source: One Architecture & Urbanism / Sherwood Design Engineers, 2023

COMMUNITY CONSIDERATIONS				
Integration with Surroundings	Environmental Stewardship	Aesthetic Value & Placemaking Potential	Permitting / Coordination Complexity	Benefit to MS4 Compliance
Low, Medium, High	Low, Medium, High	Low, Medium, High	Low, Medium, High	Low, Medium, High
Medium	Medium	High	Medium	Medium
Medium	High	Medium	Medium	Medium
Medium	Medium	Low	Medium	Low
Medium	High	Low	Low	Low
High	High	High	Low	High
Low	Medium	Medium	Low	Low
Low	Low	High	Medium	Medium
Low	Medium	Low	Low	Low
Low	Low	Low	Low	Medium
Medium	High	High	Medium	High
Medium	Medium	High	Low	Medium
Low	Low	Low	Medium	Low
Medium	Medium	High	Medium	Medium
Medium	Medium	High	Medium	Medium
Low	Medium	Medium	Medium	High
Low	High	Medium	Medium	High
Medium	High	Medium	High	High
Low	Medium	Medium	Medium	Low
Low	Low	Low	Medium	Medium
Low	Medium	Medium	Medium	Low
High	High	High	High	Medium
Medium	High	Medium	Medium	Low
High	High	High	High	Low

## GREEN INFRASTRUCTURE DESIGN OPTIONS PRIORITIZATION MATRIX NOTES

The matrix describes a way to compare green infrastructure strategies and provides select technical criteria as a starting point for analysis. All measures are industry-standard practices. Guidance is taken from the Georgia Stormwater Management Manual (GSMM), which is considered by EPA as one of the leading guidance documents for green infrastructure in the nation, in the absence of specific EPA guidance.

**Ecological Considerations** characterize design criteria and recognize the importance of co-benefits for the natural environment. They include position in the watershed based on the framework of general applicability or specific applicability to the upper, middle, or lower watershed. This category also gives an indication of the ecological co-benefits that green infrastructure can deliver, including making a contribution to the restoration of the natural environment or the provision of habitat.

**Economic Considerations** evaluate the relative cost for both one-time installation and recurring maintenance costs. Unit costs are relative due to uncertainty around site-specific conditions and the changing fiscal context, driven by inflation and supply-chain operations. Still, green infrastructure interventions are generally found to be cheaper to maintain than traditional “gray infrastructure” solutions (i.e. subsystem pipe networks) due to the self-sufficiency of the vegetation within green infrastructure.

**Community Considerations** evaluate the societal implications of green infrastructure, including the impacts that interventions have on the campus’s integration with surrounding neighborhoods, the collective campus’s environmental stewardship, contiguous campus character, compliance with governmental regulations. Evaluation of considerations related to permitting/ coordinating correspond to the level of inter-organizational coordination and scale of the project. Metrics that are evaluated in this category, with their associated considerations, include:

- **City-Campus Integration:** The degree to which the green infrastructure facilitates benefit to surrounding neighborhoods or provides connections between the campus and neighborhoods
- **Environmental Stewardship:** The degree to which an intervention contributes to the Campus’s overall sustainable use and protection of the natural environment
- **Aesthetic Value & Placemaking Opportunity:** The degree to which green infrastructure offers additional benefits to the campus in terms of improving aesthetics, facilitating continuous campus character, and orienting infrastructure around the campus employees and students.
- **Permitting/Coordinating:** The degree to which extensive permitting or inter-organizational coordination is

necessary, as a result of the scale or complexity of the measure.

- **Benefit to MS4 Compliance:** The degree to which the green infrastructure advances the Campus towards MS4 compliance by either reducing the amount of impervious area that exists or by increasing the amount of impervious area runoff that is treated by green infrastructure.

Green infrastructure strategies are evaluated based on their relative benefit to the campus or surrounding communities.

### **Stormwater Management & Cloudburst Mitigation**

The strategies that apply to managing moderate rain events can also apply to managing cloudbursts, or extreme rainfall events. A layered approach that introduces a hierarchy of flooding can ensure capacity for a range of rainfall volumes. For example, measures such as green roofs and infiltration trenches can hold a certain amount of water as rain accumulates, and as they reach capacity, stormwater could flow to and be detained in larger areas (e.g., bioretention features, detention ponds, flood management areas).

### **Application of the Matrix**

The matrix is deliberately non-determinant; it is a tool that could be used alongside and in concert with other technical and value-based evaluation frameworks and inputs to explore the

range of green infrastructure strategies that might be suitable for a given location on campus. The utility of the matrix builds on the cloudburst visioning process, which remains the fundamental step to envision the benefits and scale of green infrastructure projects.

## GREEN INFRASTRUCTURE DESIGN OPTIONS TECHNICAL CRITERIA

GREEN INFRASTRUCTURE DESIGN OPTIONS (MEASURES, BMPs)	TECHNICAL CRITERIA		
	Maximum Drainage Area	Pressure Head Needed	Maximum Slope
	Acres	Feet	%
Green Roofs	100% of BMP size	0.5 - 1	10
Rainwater Harvesting	N/A	N/A	2
Oil/Grit Separator	5	4	6
Downspout Disconnect	0.06	N/A	6
Site Reforestation/Revegetation	0.25 Min	N/A	N/A
Infiltration Trench	5	1-3	6
Permeable Pavers/Surfaces	300% of BMP size	N/A	0.5
Bioretention	10	5-8	6
Flow-Through Planters/Landscape Infiltration	10	2-6	6
Dry Bioswales	5	N/A	5
Wet Bioswales	0.06	2	6
Dry Well	0.06	2	6
Organic Filter	5	3-5	4
Surface Sand Filters	5	1	4
Dry Detention Pond	10 Min.	N/A	15
Extended Dry Detention Pond	10 Min.	N/A	15
Wet Pond	25	6-8	15
Pocket Pond	10	6-8	0
Underground Filter	5	2-5	4
Flood Management Area	N/A	N/A	N/A
Stormwater Wetland	25	3-5	8
Pocket Stormwater Wetland	5	2-3	0
Stream Restoration	N/A	N/A	N/A

Source: One Architecture & Urbanism / Sherwood Design Engineers, 2023

## NOTES

Guidance for industry-standard practices are taken from the [Georgia Stormwater Management Manual](#) (GSMM), which is considered by EPA as one of the leading guidance documents for green infrastructure in the nation, in the absence of specific EPA guidance.

### Location in watershed

Based on the priorities listed for each portion of watershed. Upper Watershed: Infiltrate, Convey Downstream; Middle Watershed: Slow Water Flows through storage, Divert Flows from Problem Areas, Convey Downstream; Lower Watershed: Absorb and Store

### Ecological co-benefits

Evaluation considers the ancillary benefits associated with the incorporation of Green Infrastructure on campus, including the provision of habitat within the Green Infrastructure and the mitigation of Urban Heat Island Effect through the decrease of impervious area or the increase of tree canopy.

### Economic considerations

Due to the unavailability of data from the federal government on Green Infrastructure standards, costs were taken from Volume 2 of the Georgia Stormwater Management Manual (2016) and [NOAA Guidance for Cost Estimations of Nature Based Solutions](#) (2020). Costs are considered in terms of price per square foot (SF) that is treated by the green infrastructure measure / design option.

### Benefit to MS4 Compliance

Evaluation based on the degree to which the GI either reduces the amount of impervious area or treats the stormwater that generates from impervious area on campus.

### Technical criteria

(maximum drainage area; pressure head needed; maximum slope)

In absence of explicit technical guidance for national-level agencies, technical information was supplemented from the [Georgia Stormwater Management Manual](#) Volume 2 (2016) which is listed on EPA's website as a resource for GI guidance and is commonly regarded among the nation's leading stormwater guidance documents.



**one architecture**  
new york city amsterdam

